

# ODYSSEY<sup>®</sup>

## BATTERY



## Technical Data Sheet

### ODP-AGM4D

(4D-1300)

#### Battery Type

- Meets the ever-increasing power demands of today's heavy vehicle applications
- Absorbed Glass Mat (AGM) with Thin Plate Pure Lead (TPPL)
- Advanced dual purpose battery for engine start and deep cycle use

#### Handling and Storage

- Can be mounted or stored in any orientation except inverted
- 2-years storage life at 68°F (20°C) without needing to charge. Recharge when the OCV is <12.6V (50% SOC).
- Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for Dangerous Goods) and ICAO (International Civil Aviation Organisation)

#### Charging and Self-Discharge

Type of charging curve	IUU
Charger voltage at 68°F (20°C)	14.4V to 14.8V
Self-discharge per month at 68°F (20°C)	1.25%
Self-discharge per month at 104°F (40°C)	5%
80% depth of discharge cycles	400

#### Power and Performance

Voltage	12
Pulse (5 second) Hot Cranking Amps (PHCA)	2400
Cold Cranking Amps (CCA)	1300
HCA	1747
MCA	1545
20Hr Nominal Capacity (Ah)	170
10Hr Nominal Capacity (Ah)	153
Reserve Capacity Minutes	370
Terminal	SAE
Torque Spec	N/A
Internal Resistance	NA
Short Circuit	NA

#### Dimensions and Weight

Length	20.4 in / 518 mm
Width	8.8 in / 224 mm
Height (terminals included)	8.6 in / 218 mm
Height (container)	8.3 in / 211 mm
Weight	117 lbs / 53.1 kg

#### Temperature

Operating temperature range	-40°F / -40°C to 140°F / +60°C
Optimum storage temperature	68°F / +20°C

#### Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

\*Cold Start Performance S.A.E J537 Apr 2016



**EnerSys World Headquarters**  
2366 Bernville Road  
Reading, PA 19605, USA  
Tel: +1-800-964-2837

**EnerSys EMEA**  
EH Europe GmbH  
Baarerstrasse 18  
6300 Zug, Switzerland

**EnerSys Asia**  
152 Beach Road  
#11-08 Gateway East  
Building  
Singapore 189721  
Tel: +65 6416 4800

Want more info?  
Scan code to access  
the ODYSSEY® Battery  
Literature Library

